

Fluid Control Valves



Pressure Regulating Valves

194 - 195

Safety Relief Valves

196

Pneumatic Valves

196

Metering Valves

197

Pressure Regulating Valves

- **Pressure regulating valves** are used to regulate pressure & protect the system when the discharge is closed
- **Multiple outlets:** in applications where more than one outlet is required a constant system pressure is maintained
- **System working pressure:** is maintained regardless of what percentage of fluid is by-passed

140 to 220 Bar - 24 Lpm



Part No.	Bar	Lpm	Code
ART 556	140	25	O
ART 60052500	220	24	O

- Brass body - S/Steel internal parts
- Max temp 90°C (ART 556 80°C)
- Mounted in-line
- 3/8" F in 3/8" F out
- 3/8" F by-pass

140 to 220 Bar - 24 to 35 Lpm



Part No.	Bar	Lpm	Code
ART 555	140	35	O
ART 60054000	170	24	O
ART 60051500	220	24	O

- Brass body - S/Steel internal parts
- Max temp 90°C (ART 555 80°C)
- Mounted off-line on a tee
- 3/8" F in
- 3/8" F by-pass

60 Bar - 200 Lpm



Part No.	Bar	Lpm	Code
TIMAX	60	200	Y

- Brass body
- S/Steel internal parts
- Max temp 60°C
- 3/4" F in 3 x 1/2" F out
- 1" F by-pass
- Manual by-pass handle

180 Bar - 200 Lpm



Part No.	Bar	Lpm	Code
ART 605100	180	200	O

- Brass body
- S/Steel internal parts
- Max temp 90°C
- Mounted off-line on a tee
- 3/4" F in
- 1/2" F by-pass

300 to 450 Bar - 200 to 450 Lpm



Part No.	Bar	Lpm	Code
RV3/300	300	450	K
RV3/450	450	200	K

- Cast iron body
- S/Steel valve & seat
- Max temp 60°C
- 1 1/4" F in
- 1 1/4" F by-pass

200 Bar - 180 Lpm



Part No.	Bar	Lpm	Code
RV2	200	180	K

- Brass body
- S/Steel valve & seat
- Max temp 60°C
- 1" F in 3/4" F out
- 1 1/4" F by-pass

280 to 400 Bar - 80 Lpm



Part No.	Bar	Code
ART 60059060	280	O
ART 60055000	400	O

- Max flow 80 Lpm
- Max temp 90°C
- 1/2" F in 1/2" F out
- 1/2" F by-pass

200 Bar - 180 Lpm



Part No.	Bar	Lpm	Code
NL2	200	180	K

- Brass body
- S/Steel valve & seat
- Max temp 60°C
- 1" F in 3/4" F out
- 1 1/4" F by-pass
- Manual by-pass handle

Pressure Regulating Valves

40 to 500 Bar - 80 to 120 Lpm

Part No.	Bar	Lpm	Code
RV1/40	40	120	K
RV1/100	100	120	K
RV1/200	200	120	K
RV1/300	300	80	K
RV1/400	400	80	K
RV1/500	500	80	K

- Brass body
- S/Steel valve & seat
- Max temp 60°C
- 2 x 3/4" F ports



40 to 500 Bar - 80 to 120 Lpm

STAINLESS
STEEL

Part No.	Bar	Lpm	Code
RX1/40	40	120	K
RX1/100	100	120	K
RX1/200	200	120	K
RX1/300	300	80	K
RX1/400	400	80	K
RX1/500	500	80	K

- Brass & S/Steel body
- S/Steel valve & seat
- Max temp 60°C
- 2 x 3/4" F ports



15 Bar

Part No.	Bar	Code
3316-0002	15	P

- Cast Iron body
- S/Steel valve cone
- 1 1/4" M in
- 1 1/4" F by-pass
- Max temp 80°C
- Mount off-line on a tee



10 to 17 Bar

Part No.	Bar	Code
3300-0015	10	P
3300-0016	17	P

- Nylon body
- Nylon valve seat
- 3/4" M in
- 3/4" F by-pass
- Max temp 60°C
- Mount off-line on a tee



15 Bar

Part No.	Bar	Code
3300-0002	15	P

- Bronze body
- S/Steel valve ball
- 1/2" M in
- 1/2" F by-pass
- Max temp 80°C
- Mount off-line on a tee



30 Bar

Part No.	Bar	Code
3300-0001	30	P

- Bronze body
- S/Steel valve ball
- 3/4" M in
- 3/4" F by-pass
- Max temp 80°C
- Mount off-line on a tee



Pneumatic & Safety Relief Valves

Pneumatic & Safety Relief Valves

- **Pneumatic valves:** operate as standard unloader, regulator & distributor valves, with remote air powered actuation
- **Safety relief valves:** are designed to protect a pump or system when its maximum pressure has been exceeded
- **Important:** safety relief valves must **never** be used in place of pressure regulator or unloader valves



Pneumatic Regulator - 200 Bar

Part No.	Bar	Lpm	Code
PN/RV2	200	180	K

- Brass body
- S/Steel valve & seat
- Max temp 60°C
- Max air press 8 Bar
- 1" F in 3/4" F out
- 1 1/4" M by-pass
- Air ports 1/4" F

Pneumatic Regulator - 160 to 300 Bar



Part No.	Bar	Lpm	Code
PN3/160	160	450	K
PN3/240	240	300	K
PN3/300	300	200	K

- Aluminium & cast iron body
- S/Steel valve & seat
- Max temp 60°C
- Max air press 6 Bar
- 1 1/2" F in 1 1/2" F out
- 1 1/2" F by-pass
- Air ports 1/4" F



Pneumatic Unloader - 200 Bar

Part No.	Bar	Lpm	Code
PN/VU2	200	180	K

- Brass body
- S/Steel valve & seat
- Max temp 60°C
- Max air press 8 Bar
- 1" F in 3/4" F out
- 1 1/2" M by-pass
- Air ports 1/4" F



Pneumatic Distributor 1400 Bar

Part No.	Bar	Lpm	Code
PN12	1400	80	K

- Brass body
- S/Steel valve & seat
- Max temp 60°C
- Max air press 8 Bar
- 3/8" F in 3/8" F out
- 3/8" F by-pass
- Air ports 1/4" F



Safety Relief Valve - 200 Bar

Part No.	Bar	Lpm	Code
SR	200	41	Y

- Brass body
- S/Steel valve & seat
- Max temp 75°C
- 3/8" M in 1/4" F out



Safety Relief Valve - 700 Bar

Part No.	Bar	Lpm	Code
S3	700	100	K

- Brass body
- S/Steel valve & seat
- Max temp 75°C
- 1/2" M inlet



Safety Relief Valve - 100 to 600 Bar

Part No.	Bar	Lpm	Code
SV2/100	100	160	K
SV2/200	200	160	K
SV2/300	300	160	K
SV2/400	400	160	K
SV2/500	500	160	K
SV2/600	600	160	K

- Brass body
- S/Steel valve & seat
- Max temp 75°C
- 1/2" M inlet



Safety Relief Valve - 1400 Bar

Part No.	Bar	Lpm	Code
SV12	1400	80	K

- S/Steel body
- S/Steel valve & seat
- Max temp 60°C
- 1/2" M inlet

Mini Relief Valve - 160 to 220 Bar



Part No.	Bar	Lpm	Code
60.0555.15	165	8-12	K
60.0555.16	165	12-16	K
60.0555.22	220	12-16	K

- Brass body
- S/Steel sealing ball
- Max temp 108°C
- 1/4" BSPM inlet - 6mm Ø hose barb discharge

Metering Valve

Part No.	Code
ART 290954	O

- Max press 30 Bar
- Max flow 10 Lpm
- Max temp 40°C
- Panel mounting
- 8mm hose barb
- Brass construction
- Viton seals



Metering Valve

Part No.	Code
ART 290945	O

- Max press 30 Bar
- Max flow 10 Lpm
- Max temp 40°C
- Panel mounting
- 8mm hose barb
- Brass construction
- Viton seals



Metering Valve

Part No.	Code
SPL 5418	O

- Manufactured in brass
- 6mm hose barbs



Metering Valve

Part No.	Code
SPL 5324	O

- Manufactured in S/Steel
- 6mm hose barbs



Twin Inlet Metering Valve

Part No.	Code
29.0900.00	O

- Max press 0.5 Bar
- Max flow 1 Lpm
- Max temp 60°C
- 8mm hose barb



Metering is proportional to knob rotation and position

Metering Valve

Part No.	Code
29.0980.00	O

- Max press 30 Bar
- Max flow 10 Lpm
- Max temp 40°C
- 8mm hose barb
- Panel mounting



Metering is proportional to knob rotation and position

Metering Valve - High Temp & Pressure

Part No.	Code
ART 29092012	O

- Max press 250 Bar
- Max flow 13 Lpm
- Max temp 80°C
- Panel mounting unit
- 1/4" M threaded ports

