

Swivels



In-Line Brass Swivels	212
In-Line Stainless Steel Swivels	212
90° Swivels	212
Polypropylene Swivels	212
Heavy Duty Dual & Triple Bearing Swivels	213
Single Bearing Hose Barb Swivels	213
90° Triple Bearing Swivels	213
Flanged Swivels	213

Swivels

LR Series Brass Swivels



Part No.	Threads	Code
26.1000.00	3/8" M x 3/8" F	O
26.1000.05	3/8" M x 1/4" F	O

- Max press 250 Bar
- Max flow 30 Lpm
- Max temp 90°C
- Teflon & Nitrile seals

MR-1 Series S/Steel Swivels



Part No.	Threads	Code
26.1060.00	1/4" M x 1/4" F	O
26.1061.00	3/8" M x 3/8" F	O

- Max press 350 Bar
- Max flow 40 Lpm
- Max temp 160°C
- Teflon & Nitrile seals

MR-0 Series Brass Swivels



Part No.	Threads	Code
26.1040.00	1/4" M x 1/4" F	O
26.1050.00	3/8" M x 3/8" F	O
26.1055.00	1/2" M x 1/2" F	O

- Max press 250 Bar
- Max flow 40 Lpm
- Max temp 160°C
- Teflon & Nitrile seals

SWIF Series S/Steel Swivels



Part No.	Threads	Code
SWIFMF1	1/2" M x 1/2" F	K

- Max press 40 Bar
- Max flow 40 Lpm
- Max temp 95°C
- Viton seals
- Ball bearing swivel

SW65 - Large Flow Brass Swivel



Part No.	Threads	Code
30.6480.00	1/2" M x 1/2" F	

- Max press 24 Bar
- Max flow 100 Lpm
- Max temp 90°C
- Teflon & Nitrile seals
- Ball bearing swivel

SW5 Series S/Steel Swivel



160 Lpm



Part No.	Threads	Code
26.1070.00	1/2" M x 1/2" F	K

- Max press 200 Bar
- Max flow 160 Lpm
- Max temp 90°C
- Viton o-rings

990 Series 90° Brass Swivels



Part No.	Threads	Code
990-6F6F-B	3/8" F x 3/8" F	O
990-6F6M-B	3/8" F x 3/8" M	O

- Max press 100 Bar
- Brass construction
- Max temp 70°C
- Buna N seals

SW90 - Brass & S/Steel



Part No.	Threads	Code
Max press 250 Bar - Max flow 40 Lpm		
26.1300.20	1/4" M x 1/4" F	O
26.1300.40	3/8" M x 3/8" F	O
Max press 350 Bar - Max flow 80 Lpm		
26.1320.00	1/2" M x 1/2" F	O

- Max flow 80 Lpm - Max press 350 Bar
- Max temp 90°C
- Teflon & Viton seals
- S/Steel bolt & nickel plated brass body

Stainless Steel Hose Tail Swivels



Part No.	Thread x Barb	Code
SWIFB13	1/2" M x 13mm	K
SWIFB16	1/2" M x 16mm	K
SWIFB19	1/2" M x 19mm	K

- Max press 40 Bar
- 316 S/Steel
- Max temp 95°C
- Viton seals

Polypropylene Swivels



Part No.	Threads	Code
SW100	1" F x 1" M	R
SW150	1 1/2" F x 1 1/2" M	R
SW200	2" F x 2" M	R

- Max press 5 Bar
- Teflon thrust bearing
- Viton seals
- S/Steel drive stud

Mosmatic Heavy Duty Swivels

- Max press 250 Bar
- Max temp 120°C
- Max speed 30 Rpm
- Nickel plated brass body
- Triple bearing system
- Stainless steel bearings
- Multiple seal system
- Totally corrosion resistant
- For water, oil, air, pH 3-12

DGL - Triple Bearing Female x Male Thread

Part No.	Female	Male	Code
31.001	1/4" BSP	1/4" BSP	K
31.003	1/4" BSP	3/8" BSP	K
31.101	3/8" BSP	1/4" BSP	K
31.103	3/8" BSP	3/8" BSP	K



DGL - Triple Bearing Female Thread

Part No.	Female	Female	Code
31.002	1/4" BSP	1/4" BSP	K
31.004	1/4" BSP	3/8" BSP	K
31.104	3/8" BSP	3/8" BSP	K



DGS - Dual Bearing Female x Male Thread

Part No.	Female	Male	Code
30.001	1/4" BSP	1/4" BSP	K
30.003	1/4" BSP	3/8" BSP	K
30.101	3/8" BSP	1/4" BSP	K
30.103	3/8" BSP	3/8" BSP	K



DGK Single Bearing Hose Barb x Thread

Part No.	Thread	Barb	Code
32.031	1/4" BSP	6mm	K
32.032	1/4" BSP	8mm	K
32.039	1/4" BSP	10mm	K
32.131	3/8" BSP	6mm	K
32.132	3/8" BSP	8mm	K
32.139	3/8" BSP	10mm	K



WDG - Triple Bearing 90° Swivels

Part No.	Female Thread	Male Thread	Code
Dimension (A) = 7mm ID - Male Thread is Tapered			
40.013	3/8" BSPF	3/8" BSPM	K
Dimension (A) = 10mm ID - Male Thread is Parallel			
40.112	3/8" BSPF	3/8" BSPM	K

- Max press 150 Bar
- Max temp 90°C
- Max speed 30 Rpm
- Nickel plated brass body
- Stainless steel bearings
- Multiple seal system
- Totally corrosion resistant
- Easy turning at high pressure
- For water, oil, air, pH 3-12



DGG - DGF Triple Heavy Duty Bulkhead Swivels

- Max press 250 Bar
- Max temp 120°C
- Max speed 30 Rpm
- Nickel plated brass body
- Triple bearing system
- Stainless steel bearings
- Multiple seal system
- Totally corrosion resistant
- For water, oil, air, pH 3-12

M22 Male x Male thread

Part No.	Male	Male	Code
33.253	M22 x 1.5 M	3/8" BSP	K



Female thread x Male thread

Part No.	Female	Male	Code
33.001	1/4" BSP	1/4" BSP	K
33.003	1/4" BSP	3/8" BSP	K
33.101	3/8" BSP	1/4" BSP	K
33.103	3/8" BSP	3/8" BSP	K



Flanged F thread x M thread

Part No.	Female	Male	Code
35.103	3/8" BSP	3/8" BSP	K



90° M22 Male x Male thread

Part No.	Male	Male	Code
33.553	M22 x 1.5 M	3/8" BSP	K

