

66 & 66HP Series - Industrial Motor Pump Units



200 to 300 Bar - 21 to 41 Lpm

Part No.	Bar	Lpm	Volts	HP	(LxWxH) mm	Kg
M100-1050	200	35	415	20.5	970 x 490 x 440	132
M100-1051	210	41	415	25	970 x 490 x 440	149
M100-1052	250	29	415	20.5	970 x 490 x 440	132
M100-1053	300	21	415	20.5	970 x 490 x 440	132
Motor & Pump Speed 1450 Rpm						
Mounting hole centres width 395mm - length 810mm						
20.5 Hp - Max xx Amps (Approx) in Star - Max xxx Amps in Delta						
25 Hp - Max 34.3 Amps (Approx) in Star - Max 59.3 Amps in Delta						

- Interpump 66 series pumps
- Vibroflex drive coupling & flange
- Motor protection to IP55
- 3/4"BSPF inlet
- 3/8"BSPF outlet
- Max temp 60°C

350 to 500 Bar - 15 to 23 Lpm

Part No.	Bar	Lpm	Volts	HP	(LxWxH) mm	Kg
M100-1060	350	23	415	20.5	970 x 490 x 440	149
M100-1061	400	18	415	20.5	970 x 490 x 440	149
M100-1062	500	15	415	20.5	970 x 490 x 440	149
M100-1063	500	18	415	25	970 x 490 x 440	149
Motor & Pump Speed 1450 Rpm						
Mounting hole centres width 395mm - length 810mm						
Max 34.3 Amps (Approx) in Star - Max 59.3 Amps in Delta						

- Interpump 66HP series pumps
- Vibroflex drive coupling & flange
- Motor protection to IP55
- 1/2"BSPF inlet
- 3/8"BSPF outlet
- Max temp 60°C

Optional Extras - Regulators, Safety Valves, Water Filters - Subject to application

When operating at temperatures above 40°C certain installation conditions must be observed, please contact our sales office for full details