



300P-LC

**1060
Lpm**

**2.5
Bar**

**25m
Head**

**Petrol
Loncin**

Petrol

300P-LC

1060

2.5

Lpm

Bar

LONCIN



Pairing the class leading Pacer S Pump and the Loncin 6.5hp G200F engine gives a great balance of high performance and affordability. The 2" pump is available with high flow or high pressure impeller with flows up to 871 Lpm and pressures up to 4 Bar. The 3" pump offers flows up to 1060 Lpm.



**Loncin G200F
Engine**

Pump

Make	Pacer
Model	S Series - SE3SL
Max Flow	1060 Lpm
Max Pressure	2.5 Bar
Body	Corrosion resistant polyester
Seals	EPDM (Buna & Viton available)
Mechanical seal	Carbon ceramic
Impeller	Polyester 975 - 4 vane
Inlet & Outlet	3" NPT female (BSP available)
Suction lift	Up to 7.6m
Notes	Self priming after initial prime

Engine

Make	Loncin
Model	G200F-P
Power	6.5Hp - Gross
Shaft	3/4" parallel keyway shaft
Fuel capacity	3.6 Litres
Lubrication	Oil splash
Oil alert	Low level engine shutdown system
Cooling	Air cooled
Fuel system	Carburettor
Starting	Recoil
Ignition	Transistorised pointless

Weight & Dimensions

Weight	20.5 Kg
Dimensions	L540 - W400 - H345 mm

Dealer Stamp