



E100-1013



**21
Lpm**

**200
Bar**

**2900
Psi**

**Petrol
Honda**


E100-1013

21
Lpm

200
Bar



POWERED by
HONDA



**Interpump
59 Series**



**Honda GX390
Engine**

General

Weight	61Kg
Dimensions	L720 - W460 - H500 mm
Frame	HD skid with 4x anti-vibration rubbers
Unloader valve outlet	3/8" BSP female thread
Unloader valve bypass	15mm hose barb
Suction filter inlet	3/4" hose barb
Max fluid temperature	60°C

Pump & Auxiliaries

Make & Model	Interpump 59 series - E3B2121M
Flow	21 Lpm
Pressure	200 Bar - 2900 Psi
Lubrication	Oil splash
Materials	Nickel plated brass manifold
Speed	1450 Rpm
Drive	Interpump RS500 reduction gearbox
Pressure control	VRT3 adjustable unloader valve
By-pass system	External return to tank system

Engine

Make	Honda
Model	GX390K1QX
Power	13Hp - Gross / 11.7Hp - Net*
Fuel capacity	6.5 Litres
Lubrication	Oil splash
Oil alert	Low level engine shutdown system
Cooling	Air cooled
Fuel system	Carburettor
Starting	Recoil
Ignition	Transistorised pointless

*Net power @ 3600 Rpm in accordance with SAE J1349

Dealer Stamp

