



LC SERIES

Petrol



**15
Lpm**

**250
Bar**

**3626
Psi**

**Petrol
Loncin**

Part No:

LCT15250PLR

Pressure: 250 Bar - 3626 Psi

Flow: 15 Lpm

Pump: Interpump 59 Series - E3B2515

Pump drive: Interpump RS500 gearbox drive - 1450 Rpm

Engine: Loncin G420F-P5 with oil alert

Starting: Manual recoil start

Fuel capacity: 6.5 Litres

Pressure control: Return to tank unloader valve with external chemical injector

Priming aid: Easy prime ball valve fitted to pump manifold

Trolley: Powder coated trolley - 13" wheels

Dimensions: 855L x 625W x 1055H (mm)

Weight: 73 Kg

LC SERIES

Part No. LCT15250PLR



Petrol	15	250	3626
	Lpm	Bar	Psi

Pairing the class leading Interpump Pump and the Loncin 12hp G420 engine gives a great balance of high performance and affordability.



Powered by
LONCIN

Accessories

Lance Assembly



Part No:
200-1005-040

900mm straight lance with MV925 trigger & 15° 04 nozzle - M22 M inlet

High Pressure Hose



Part No:
HP2600KK

10m of 3/8" wire braided synthetic rubber hose - M22F x M22 F fittings

Suction Hose



Part No:
209-1034HD

3m of wire reinforced PVC hose with 50 mesh weighted filter

Chemical Hose



Part No:
209-1006

1.5m of 6mm clear PVC hose with weighted chemical filter

Dealer Stamp