



DIAPHRAGM PUMP 12 VOLT

2.2 GPM
8.3 L/min

AVAILABLE
PORT OPTIONS

QA QUICK ATTACH PORTS

3/8" NPT PORTS

- Polypropylene Pump Housing and Valve Plate
- Zinc Plated Steel Fasteners
- Painted Steel 3" Motor Shell
- 3/8" FNPT & QA Port Options
- CE Approved
- 70 PSI (4.8 Bar) Max
- 2.2 GPM (8.3 LPM) Max
- Self Priming to 8 Feet
- Max Fluid Temp 140 Deg. F
- 12V DC
- 8.0 Max Amps
- 4.8 lbs Dry



**CORROSION RESISTANT VITON® VALVES
AND SANTOPRENE™ DIAPHRAGM.**

INLINE FUSE PROTECTION

Honeywell
MICRO SWITCH™

APPROVED FOR USE WITH
Roundup®
AGRICULTURAL HERBICIDES

MODEL	DESCRIPTION	PORTS	PACKAGING	UPC
EF2200	2.2 GPM 12 Volt Diaphragm Pump	3/8" FNPT	Bulk	N/A
EF2200-BC	2.2 GPM 12 Volt Diaphragm Pump	3/8" FNPT	Barcoded	81448501343-7
EF2200-BOX	2.2 GPM 12 Volt Diaphragm Pump	3/8" FNPT	Boxed	81448501040-5
EF2200-QA	2.2 GPM 12 Volt Diaphragm Pump	QA	Bulk	N/A
EF2200-QA-BOX	2.2 GPM 12 Volt Diaphragm Pump	QA	Boxed	81448501378-9
EF2000-KIT	2.2 GPM Replacement Head, Fully Assembled	3/8" FNPT	Boxed	81448501338-3
EF2200-QA-KIT	2.2 GPM Replacement Head, Fully Assembled	QA	Boxed	81448501864-7

TECHNICAL SPECIFICATIONS

Pressure PSI/Bar	Current (Amps)	Flow GPM/LPM
0/0	4.2	2.20/8.33
10/1.7	4.8	2.00/7.57
20/1.4	5.4	1.84/6.97
30/2.1	6.1	1.69/6.40
40/2.8	6.6	1.58/5.98
50/3.4	7.3	1.48/5.60
60/4.1	7.8	1.35/5.11

