



DIAPHRAGM PUMP 12 VOLT

4.0 GPM
15.1 L/min

AVAILABLE
PORT OPTIONS

QA QUICK ATTACH PORTS

1/2" NPT PORTS

- Polypropylene Pump Housing and Valve Plate
- Zinc Plated Steel fasteners
- Painted Steel 3" Motor Shell
- 1/2" FNPT & QA Port Option
- CE Approved
- 60 PSI (4.1 Bar) Max
- 4.0 GPM (15.1 LPM) Max
- Self Priming to 8 Feet
- Max Fluid Temp 140 Deg F
- 12V DC
- 13.0 Max Amps
- 5.6 lbs Dry



**CORROSION RESISTANT VITON® VALVES
AND SANTOPRENE™ DIAPHRAGM.**

INLINE FUSE PROTECTION

Honeywell
MICRO SWITCH™

APPROVED FOR USE WITH
Roundup®
AGRICULTURAL HERBICIDES

MODEL	DESCRIPTION	PORTS	PACKAGING	UPC
EF4000	4.0 GPM 12 Volt Diaphragm Pump	1/2" FNPT	Bulk	N/A
EF4000-BC	4.0 GPM 12 Volt Diaphragm Pump	1/2" FNPT	Barcoded	81448501345-1
EF4000-BOX	4.0 GPM 12 Volt Diaphragm Pump	1/2" FNPT	Boxed	81448501042-9
EF4000-QA	4.0 GPM 12 Volt Diaphragm Pump	QA	Bulk	N/A
EF4000-QA-BOX	4.0 GPM 12 Volt Diaphragm Pump	QA	Boxed	81448501380-2
EF4000-KIT	4.0 GPM Replacement Pump Head, Fully Assembled	1/2" FNPT	Boxed	81448501340-6
EF4000-QA-KIT	4.0 GPM Replacement Pump Head, Fully Assembled	QA	Boxed	81448501866-1

TECHNICAL SPECIFICATIONS

Pressure PSI/Bar	Current (Amps)	Flow GPM/LPM
0/0	6.2	4.8/18.17
10/.7	7.5	4.6/17.41
20/1.4	9.1	4.2/15.90
30/2.1	10.6	3.8/14.38
40/2.8	11.7	3.5/13.25
50/3.4	12.7	3.2/12.11
60/4.1	N/A	N/A

