



DIAPHRAGM PUMP 12 VOLT

7.0 GPM
26.5 L/min

AVAILABLE
PORT OPTIONS

QA QUICK
ATTACH
PORTS

1/2" NPT
PORTS

- Polypropylene Pump Housing and Valve Plate
- Zinc Plated Steel fasteners
- Painted Steel 3" Motor Shell
- 1/2" FNPT & QA Port Option
- CE Approved
- 60 PSI (4.1 Bar) Max
- 7.0 GPM (26.5 LPM) Max
- Self Priming to 12 Feet
- Max Fluid Temp 140 Deg F
- 12V DC
- 23.0 Max Amps
- 9.5 lbs Dry



**CORROSION RESISTANT VITON® VALVES
AND SANTOPRENE™ DIAPHRAGM.**

INLINE FUSE PROTECTION

Honeywell
MICRO SWITCH™

APPROVED FOR USE WITH
Roundup®
AGRICULTURAL HERBICIDES

MODEL	DESCRIPTION	PORTS	PACKAGING	UPC
EF7000-BOX	7.0 GPM 12 Volt Diaphragm Pump	1/2" FNPT	Boxed	81448501200-3
EF7000-QA-BOX	7.0 GPM 12 Volt Diaphragm Pump	QA	Boxed	81448501584-4
EF7000-KIT	7.0 GPM Replacement Pump Head, Fully Assembled	1/2" FNPT	Boxed	81448501585-1
EF7000-QA-KIT	7.0 GPM Replacement Pump Head, Fully Assembled	QA	Boxed	81448501868-5

TECHNICAL SPECIFICATIONS

Pressure PSI/Bar	Current (Amps)	Flow GPM/LPM
0/0	10	7.2/27.2
10/.7	12	6.8/25.7
20/1.4	14	6.4/24.2
30/2.1	16	6.0/22.7
40/2.8	18	5.6/21.2
50/3.4	20	5.2/19.7
60/4.1	N/A	N/A

