

HP SERIES PUMP 12 VOLT

2.0 GPM 7.5 L/min

AVAILABLE PORT OPTIONS

QA QUICK ATTACH PORTS

200PSI

HIGH PRESSURE PUMP FOR SPOT AND BROADCAST SPRAYING APPLICATIONS

- Automatic Shut-Off to Conserve Battery Life
- Ceramic Coated Plunger ProlongsSeal Life
- QA Ports
- CE Approved
- 200 PSI (13.7 Bar) Max
- 2.0 GPM (7.5 LPM) Max
- Max Fluid Temp 140 Deg F
- 12V DC
- 20.0 Max Amps
- 13.0 lbs Dry
- Includes 6 Common Fittings



INCLUDES VARIABLE PRESSURE REGULATOR.

INLINE FUSE PROTECTION

INCLUDES SIX COMMON FITTINGS

APPROVED FOR USE WITH Roundup® AGRICULTURAL HERBICIDES

MODEL	DESCRIPTION	PORTS	PACKAGING	UPC
EFHP2000	2.0 GPM 12 Volt High Pressure Plunger Pump	QA	Bulk	N/A
EFHP2000-BOX	2.0 GPM 12 Volt High Pressure Plunger Pump	QA	Box	81448501632-2

TECHNICAL SPECIFICATIONS

Pressure PSI/Bar	Current (Amps)	Flow GPM/LPM
0/0.0	6.0	2.0/7.5
50/3.4	9.0	1.75/6.6
100/6.9	12.0	1.50/5.7
150/10.3	15.0	1.40/5.3
200/13.8	17.0	1.30/4.9



