

**3" Full
Port Poly!**

2014 NEW

FEATURES

- Lightweight.
- Unrestricted 3" flow.
- Minimal fluid spillage.
- Easy to use.
- Economical.
- Reduces risk of exposure.
- Wide range of chemical resistance.
- Cannot be uncoupled in open position.
- Spillage Data: 3" = 25 ml
- Maximum operating pressure 100 P.S.I.
@ 70°F or 75 P.S.I. @ 150°F.

APPLICATIONS

- Agriculture
- Industrial
- Pharmaceutical
- Chemical processing



Male & Female shown coupled together.
Male & Female sold separately as shown below.

PREVENTS ACCIDENTAL SPILLS AND EXPOSURE!

3" FULL PORT POLY DRY-MATE						
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	
DM300AFP	3" FP Male x 3" Female NPT Threads w/ FKM(viton type) Seals	100	3"	3"	1	
DM300DFP	3" FP Female x 3" Female NPT Threads w/ FKM(viton type) Seals	100	3"	3"	1	

User friendly: Operating a Banjo Dry-Mate is simple.

The handles interlock making it easy to identify which handle opens or closes first. No guessing involved! The two Dry-Mate halves couple together with cam levers for positive engagement.

Design: The Banjo Dry-Mate is designed for safe and easy spill free connections. The "double ball" design allows maximum flow, while the cam lever style of connection is the most recognized fluid connector.

Female Dry-Mate
DM300DFP



Male Dry-Mate
DM300AFP



Male & Female Sold Separately

