

3-Way Electric Valves

2" Full Port Threaded w/Flanged Inlet

ELECTRIC VALVES

FEATURES

- 316 stainless steel ball & stem.
- Stainless steel hardware.
- Fiberglass reinforced polypropylene.
- Glass reinforced PTFE seats.
- FKM (viton type) or EPDM O-rings.
- 12-volt DC operated.
- 24-volt available in most models.
- 150 P.S.I. maximum pressure @ 70°F.
- Easily repairable.
- Open/closed indicator.



Attention:
3-Way regulating valves are not shown, but are available.
Standard 3-Way valves use the On/Off wiring diagram.



BOTTOM LOAD



SIDE LOAD

1 1/4 SECOND RESPONSE TIME

2" FULL PORT BOTTOM LOAD ELECTRIC VALVES						
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	PRICE EA
EV204BLFP	2" Full Port Electric Valve	150	2"	2"	1	

BOTTOM LOAD:
Directional flow right or left.
Valve flow cannot be turned off.

1 1/4 SECOND RESPONSE TIME

2" FULL PORT SIDE LOAD ELECTRIC VALVES						
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	PRICE EA
EV204SLFP	2" Full Port Electric Valve	150	2"	2"	1	

SIDE LOAD:
Directional flow right or left.
Valve flow cannot be turned off.

