

CT CHIERICI TITO s.r.l.		09/11/09		GB			
UNIVERSAL GUN							
RED TRIGGER P/N 15.0003.11 FEATURES: * Body and sealing seat in polypropylene reinforced with fiberglass. * Pin in stainless steel AISI 303 * Seal obtained by ball in tempered stainless steel AISI 420 and spring in stainless steel AISI 302 * Seals in NBR * Rear fluid entry * Inlet / Outlet G 1/2 F * Max Pressure 25bar – 2.5Mpa (363psi) * Max Flow rate 70 l/min (18.5 USGp.m.) * Max temperature 50°C (120° F) * Weight 131 gr (4.62 oz.)		BLUE TRIGGER P/N 15.0003.12 FEATURES: * Body and sealing seat in polypropylene reinforced with fiberglass * Pin in stainless steel AISI 303 * Seal obtained by ball in tempered stainless steel AISI 420 and spring in stainless steel AISI 302 * Seals in VITON * Rear fluid entry * Inlet / Outlet G 1/2 F * Max Pressure 25bar – 2.5Mpa (363psi) * Max Flow rate 70 l/min (18.5 USGp.m.) * Max temperature 50°C (120° F) * Weight 131 gr (4.62 oz.)		GREY TRIGGER P/N 15.0013.12 FEATURES: * Body and sealing seat in polypropylene reinforced with fiberglass * Pin in stainless steel AISI 316 * Seal obtained by ball in stainless steel AISI 316 and spring in stainless steel AISI 316 * Seals in VITON * Rear fluid entry * Inlet / Outlet G 1/2 F * Max Pressure 25bar – 2.5Mpa (363psi) * Max Flow rate 70 l/min (18.5 USGp.m.) * Max temperature 50°C (120° F) * Weight 131 gr (4.62 oz.)		BROWN TRIGGER P/N 15.0015.12 FEATURES: * Body and sealing seat in polypropylene reinforced with stapled fiberglass * Pin in stainless steel AISI 316 * Seal obtained by ball in stainless steel AISI 316 and spring in stainless steel AISI 316 * Seals in VITON * Rear fluid entry * Inlet / Outlet G 1/2 F * Max Pressure 25bar – 2.5Mpa (363psi) * Max Flow rate 70 l/min (18.5 USGp.m.) * Max temperature 50°C (120° F) * Weight 131 gr (4.62 oz.)	
GREEN TRIGGER P/N 15.0014.12 FEATURES: * The gun always leaks a small quantity of fluid Pressure loss: 2.8bar – 0.3Mpa (40psi) equal to 1–1.3 l/min 0.3 USGp.m. * Body and sealing seat in polypropylene reinforced with fiberglass * Pin in stainless steel AISI 316 * Seal obtained by ball in stainless steel AISI 316 and spring in stainless steel AISI 316 * Seals in VITON * Rear fluid entry * Inlet / Outlet G 1/2 F * Max Pressure 25bar – 2.5Mpa (363psi) * Max Flow rate 70 l/min (18.5 USGp.m.) * Max temperature 50°C (120° F) * Weight 131 gr (4.62 oz.)		YELLOW TRIGGER P/N 15.0003.10 FEATURES: * Body and sealing seat in polyamide reinforced with fiberglass * Pin in stainless steel AISI 303 * Seal obtained by ball in tempered stainless steel AISI 420 and spring in stainless steel AISI 302 * Seals in VITON * Rear fluid entry * Inlet / Outlet G 1/2 F * Max Pressure 60bar – 6Mpa (870psi) * Max Flow rate 70 l/min (18.5 USGp.m.) * Max temperature 60°C (140° F) * Weight 162 gr (5.7 oz.)		DIMENSIONAL DRAWING			