

PVC COUPLERS AND ADAPTERS

FEATURES

- Use with PVC pipe
- Easy to install
- Socket solvent weld (cement)
- Stainless steel handles, rings & pins
- EPDM gaskets standard
- Economical
- Weather & corrosion resistant

X STYLE, CAM ADAPTER (WITH SLIP FIT)

ITEM	DESCRIPTION	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	3"
X	X Style, Cam Adapter	050-X	075-X	100-X	125-X	150-X	200-X	300-X

Y STYLE, CAM COUPLER (WITH SLIP FIT)

ITEM	DESCRIPTION	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	3"
Y	Y Style, Cam Coupler	050-Y	075-Y	100-Y	125-Y	150-Y	200-Y	300-Y

WARNING: To prevent accidental opening fully engage and secure handles prior to pressurizing.

Size 1/2"-2"
Operating Pressure
 105 psi max @ 72° F
 90 psi max @ 80° F
 65 psi max @ 100° F
 25 psi max @ 140° F

Size 3"
Operating Pressure
 75 psi max @ 72° F
 68 psi max @ 80° F
 50 psi max @ 100° F
 20 psi max @ 140° F

X



Y

