

	EQUIPAGGIAMENTI TECNICI LAVAGGIO	EIETTORI DETERGENTE <i>DETERGENT INJECTOR</i>	①	7
			GB	



TABELLA PORTATE CONSIGLIATE RECOMMENDED FLOW CHART

UGELLO mm	NOZZLE inch.	PORTATA CONSIGLIATA l/min	RECOMMENDED FLOW USG p.m.
Ø1.2	0.047"	3 ÷ 5	0.79 ÷ 1.32
Ø1.5	0.059"	5 ÷ 8	1.32 ÷ 2.11
Ø1.8	0.071"	8 ÷ 12	2.11 ÷ 3.17
Ø2.1	0.083"	10 ÷ 15	2.64 ÷ 3.96
Ø2.3	0.090"	12 ÷ 18	3.17 ÷ 4.76
Ø2.5	0.098"	14 ÷ 22	3.70 ÷ 5.81
Ø2.7	0.106"	17 ÷ 26	4.49 ÷ 6.87

N.B. GLI EIETTORI DETERGENTE FUNZIONANO SOLO SE LA CONDOTTA IN USCITA DALL' INIETTORE (OUT) E' IN BASSA PRESSIONE; UTILIZZARE TUBO ADEGUATO ALLA PORTATA EVITANDO STROZZATURE E GOMITI.

N.B. THE DETERGENT INJECTORS FUNCTION ONLY IF THE EXIT CHANNEL FROM THE INJECTOR (OUT) IS AT LOW PRESSURE; USE AN APPROPRIATE TUBE FOR THE FLOW THAT AVOIDS CHOKING AND BENDS.

