


	EQUIPAGGIAMENTI TECNICI LAVAGGIO	LANCIA S6 PER PISTOLA RL600 LANCE S6 FOR SPRAY GUN RL600 40.0160.80 – 40.0160.12	(I)	29/03/02
			(GB)	1
			10.9125.00	



(I)

ISTRUZIONI PER IL MONTAGGIO

- Bloccare in morsa la chiave ES 24 pos.2 e inserire la pistola pos.1 nella sede chiave.
- Applicare sui filetti del tubo pos.3 un liquido frenafili forte (ad esempio Loctite 638) e avvitare il nipplo porta ugello pos.4 insieme al tubo usando una chiave dinamometrica ES 24 pos.5 alla coppia sopra indicata.
- Spostare la protezione pos.6 per coprire ES 24 della pistola.
- Serrare la manopola pos.7 con chiave dinamometrica ES 17 pos.8 alla coppia sopra indicata.

(GB)

ASSEMBLY INSTRUCTIONS

- Clamp in a vice the ES24 spanner (pos.2) and position the spray gun (pos.1) in the spanner lock slot.
- Apply to the thread of the Lance tube (pos.3) a strong glue (ex.Loctite 638) and tighten the nozzle (pos.4) to the tube using a Dynamometric spanner ES24 (pos.5) to obtain the described specifications.
- Move the tube protection (pos.6) to cover ES24 of the spray gun.
- Tighten the handle (pos.7) with a ES17 Dynamometric spanner (pos.8) to the described specifications.